



RENZACCI



DRYTOWER

2509 - 2511

| | | | | | | 2509 | 2511 | | | 2509 | 2511 |
|----------------------------|-------------------------|---------------------------|------------------------|--------------------------|-------|--------|------------------|------------------|---------|--------|--------|
| W A S H | Capacità | Capacité | Capacidad de carga | Beladegewicht | kg | 9 | 11 | Load Capacity | lbs | 20 | 25 |
| | Volume | Volume | Volumen | Volumen | lt | 88 | 107 | Volume | Us.Gals | 23.2 | 28.2 |
| | Diametro | Diamètre | Diámetro | Durchmesser | mm | 545 | 590 | Diameter | in | 21.8 | 23.3 |
| | Profondità | Profondeur | Profundidad | Tiefe | mm | 365 | 380 | Depth | in | 14.6 | 15 |
| | Bocca di carico | Porte de chargement | Puerta de carga | Ladetür | mm | 324 | 325 | Loading door | in | 13 | 12.8 |
| | Velocità Centrifuga | Essorage | Centrifuga | Schnellschleudern | rpm | 1100 | 1000 | Speed extract | rpm | 1100 | 1000 |
| | Fattore G | Facteur G | Factore G | G Faktor | - | 369 | 327 | G-factor | - | 369 | 327 |
| | Ingresso acqua fredda | Entrée eau froide | Entrada agua fria | Kaltwasseranschluß | Ø | 3/4" | 3/4" | Cold water inlet | Ø | 3/4" | 3/4" |
| | Ingresso acqua calda | Entrée eau chaude | Entrada agua caliente | Warmwasseranschluß | Ø | 3/4" | 3/4" | Hot water inlet | Ø | 3/4" | 3/4" |
| | Ingresso vapore | Entrée vapeur | Entrada vapor | Dampfzufuhr | Ø | 1/2" | 1/2" | Steam inlet | Ø | 1/2" | 1/2" |
| | Scarico acqua | Vidange eau | Descarga de agua | Wasserablaß | Ø | 1 1/2" | 1 1/2" | Water drain | Ø | 1 1/2" | 1 1/2" |
| | Pressione Acqua | Pression eau | Presión agua | Wasserdruck | bar | 5 | 5 | Water pressure | psi | 72,5 | 72,5 |
| | Pressione Vapore | Pression vapeur | Presión vapor | Dampfdruck | bar | 5 | 5 | Steam pressure | psi | 72,5 | 72,5 |
| Motore/Inverter | Moteur/Inverter | Potencia motor/inverter | Motor/Inverterleistung | kW | 0,55 | 1,1 | Motor/Inverter | kW | 0,55 | 1,1 | |
| Resistenze elettriche | Resistances electriques | Resistencia calentamiento | Heizwiderstände | kW | 6 | 6 | Heating elements | kW | 6 | 6 | |
| D R Y | Portata | Capacité | Capacidad | Ladevermögen | Kg | 10 | 10 | Capacity | lbs | 22 | 22 |
| | Diametro | Diamètre | Diámetro | Durchmesser | mm | 695 | 695 | Diameter | in | 27.36 | 27.36 |
| | Profondità | Profondeur | Profundidad | Tiefe | mm | 570 | 570 | Depth | in | 22.5 | 22.5 |
| | Volume | Volume | Volumen | Inhalt | dm³ | 216 | 216 | Volume | cu.ft. | 7.62 | 7.62 |
| | Giri cesto | Tours tambour | Vueltas | Trommel | rpm | 40 | 40 | Revol. of drum | rpm | 40 | 40 |
| | Inverter | Inverter | Inverter | Frequenzumrichterantrieb | Kw | 0,55 | 0,55 | Inverter | Kw | 0,55 | 0,55 |
| | Motore Cesto | Moteur | Motor | Trommelmotor | Kw | 0,37 | 0,37 | Drum Motor | Kw | 0,37 | 0,37 |
| | Ventilatore | Ventilateur | Ventilador | Ventilator | Kw | 0,25 | 0,25 | Fan motor | Kw | 0,25 | 0,25 |
| | Entrata gas | Entrée gaz | Entrada gas | Gaszufuhr | Ø | 1/2" | 1/2" | Gas inlet | Ø | 1/2" | 1/2" |
| | Entrata vapore | Entrée vapeur | Entrada vapor | Dampfzufuhr | Ø | 1/2" | 1/2" | Steam inlet | Ø | 1/2" | 1/2" |
| | Scarico aria | Evacuation air | Descarga aire | Entlüftung | mm | 195 | 195 | Air exhaust | in | 7.67 | 7.67 |
| | Potenza: | Puissance: | Potencia: | Leistung: | | | | Power: | | | |
| | Vers. gas | Version gaz | Gas | Gaszufuhr | cal/h | 15000 | 15000 | Gas | BTU | 59500 | 59500 |
| Vers. elettrico | Version électrique | Electricidad | Elektrizität | Kw | 9/12 | 9/12 | Electricity | Kw | 9/12 | 9/12 | |
| Vers. vapore | Version vapeur | Vapor | Dampf | Kg/h | 22 | 22 | Steam | lbs/h | 48.5 | 48.5 | |
| Dimensioni: | Dimensions: | Medidas: | Ausmaße: | | | | Dimensions: | | | | |
| Larghezza | Largeur | Ancho fachada | Breite | mm | 750 | 785 | Length | in | 29.5 | 30.9 | |
| Profondità | Profondeur | Profundidad | Tiefe | mm | 970 | 970 | Depth | in | 38.2 | 38.2 | |
| Altezza | Hauteur | Altura | Höhe | mm | 2140 | 2200 | Height | in | 84.2 | 86.6 | |
| Peso | Poids | Peso | Gewicht | Kg | 345 | 355 | Weight | lbs | 156.5 | 161 | |

DESIGN PERSONALIZZATO

SEMPLICITA' DI UTILIZZO

OBLÒ DI CARICO "MAXILOAD" MAGGIORATO

FACILITÀ DI CARICO E SCARICO

ALTISSIMA EFFICIENZA ED ABBATTIMENTO DEI CONSUMI



PERSONALISIERTES DESIGN

EINFACHE BENUTZUNG

"MAXILOAD" VERGRÖßERTE LADETÜR

LEICHTE BE- UND AUSLADUNG

HÖCHSTE WIRKSAMKEIT UND REDUKTION DES VERBRAUCHS



DESIGN PERSONNALISE

SIMPLICITÉ D'UTILISATION

HUBLOT DE CHARGEMENT "MAXILOAD" MAJORE

FACILITE DE CHARGEMENT ET DECHARGEMENT

TRES GRANDE EFFICACITE ET DIMINUTION DES CONSOMMATIONS

PERSONALIZED DESIGN

EASY USE

„MAXILOAD“ INCREASED LOADING DOOR

EASY LOADING AND UNLOADING

HIGH EFFICIENCY AND REDUCTION OF THE CONSUMPTIONS



DESIGN PERSONALIZADO

SENCILLEZ DE USO

PUERTA DE CARGA "MAXILOAD" MAYOR

FACILIDAD DE CARGA Y DESCARGA

ALTA EFICIENCIA Y REDUCCION DE LOS CONSUMOS



Descrizioni, dati, misure, colori, non sono impegnativi e possono variare senza alcun preavviso - Descriptions, poids, mesures, figures et couleurs sont données sans engagement de notre part - Beschreibungen, Gewichte, Maße, Bilder und Farben sind unverbindlich - Descripción, datos, medidas y colores se facilitan sin compromiso u pueden ser variados sin previo aviso - Description, weights, measurements, pictures are not binding.



Via morandi, 13 - 06012 CITTA'DI CASTELLO (PG)- ITALY
 Telefono +39-075-862961 - Fax +39-075-8559020
 E-MAIL: renzacci@renzacci.it
 INTERNET: http://www.renzacci.it